

IN THE CLAIMS:

Please amend the claims as shown below:

1. to 12. (Cancelled)

13. (Currently Amended) An imaging apparatus for recording captured images, the imaging apparatus comprising:

a connector component that connects an image storage component, that stores a plurality of image data, to the imaging apparatus in a removable condition;

a retrieve condition storage component that stores retrieve condition data, such as a key image or a keyword, for use as a retrieve condition when performing image retrieval ~~with respect to the image data stored in the image storage component connected to the connector component;~~

a retrieval component that retrieves a retrieval result by searching for [[the]] image data that matches or is similar to the retrieve condition data from among the plurality of image data stored in the image storage component connected to the connector component; and

an internal storage component that ~~accumulatively~~ stores the retrieval result retrieved by the retrieval component.

~~wherein image data that was retrieved until there is an explicit delete instruction, even [[when]]~~ in a case where the image storage component [[was]] is detached from the connector component [[or was]] and is replaced with another image storage component, the retrieval component further retrieves a retrieval result from among

a plurality of image data stored in said another image storage component using the common retrieve condition data which has been used with respect to the image storage component, and

wherein the internal storage component accumulatively stores the retrieval results retrieved by the retrieval component until there is an explicit delete instruction.

14. to 15. (Cancelled)

16. (Currently Amended) The imaging apparatus according to claim [[14]]
13, further comprising:

a power deactivation switch that instructs that the power of the imaging apparatus be deactivated;

a non-volatile storage component for saving the retrieve condition data when there is an instruction to deactivate the power from the power deactivation switch;
and

a read/write control component that, when the power to the imaging apparatus is reactivated, reads the retrieve condition data from the non-volatile storage component to write the retrieve condition data in the retrieve condition storage component.

17. (Currently Amended) The imaging apparatus according to claim 13,
further comprising:

a non-volatile storage component;

a selection component that selects whether or not to store the retrieve condition data on the non-volatile storage component when the image retrieval processing ends; and

a write control component that writes the retrieve condition data on the non-volatile storage component when a selection is made to store the retrieve condition data on the non-volatile storage component.

18. (Currently Amended) The imaging apparatus according to claim 13 further comprising:

a flag control component that sets a flag showing that retrieval is in progress at the start of image retrieval processing by the retrieval component and resets the flag at the end of the image retrieval processing;

a flag determination component that determines whether the flag is set when the power of the imaging apparatus is activated;

a first message display component that, when the flag had been set, displays a message to inquire whether or not to continue the image retrieval processing;

a first input component that inputs an instruction as to whether or not to continue the image retrieval processing; and

a first continuation instruction component that, ~~[[when]]~~ in a case where an instruction to continue the image retrieval processing ~~[[was]]~~ is input, instructs the retrieval component to continue the image retrieval processing.

19. (Currently Amended) The imaging apparatus according to claim 13 ,
further comprising:

a second message display component that, when an instruction is given to
execute the image retrieval processing, displays a message to inquire whether or not to
change the retrieve condition data;

a second input component that inputs an instruction to change the retrieve
condition data; and

a change component that changes the retrieve condition data when an
instruction is input to change the retrieve condition data.

20. (Currently Amended) The imaging apparatus according to claim 13,
further comprising:

a third message display component that, when the image retrieval
processing ends for an arbitrary image storage component, displays a message to inquire
whether or not to replace the image storage component with a different image storage
component and continue the image retrieval processing;

a third input component that inputs an instruction as to whether or not to
continue the image retrieval processing; and

a second continuation instruction component that, when an instruction to
continue the image retrieval processing is input and the different image storage component
is connected to the connector component, instructs the retrieval component to continue the
image retrieval processing.

21. (Currently Amended) The imaging apparatus according to claim 13 ,
further comprising:

a writing component that, when the image retrieval processing based on the
retrieve condition data ends, writes completion information indicating the completion of
the image retrieval processing based on the retrieve condition data onto the image storage
component that is connected to the connector component;

a detection component that detects that the image storage component on
which the completion information is stored ~~[[was]]~~ is connected to the connector
component; and

a fourth message display component that, when the connection is detected
by the detection component, displays a message indicating that the image retrieval
processing for the retrieve condition data has been completed.

22. (Currently Amended) A method for controlling an imaging apparatus
that records captured images, the method comprising the steps of:

connecting an image storage component₁ that stores a plurality of image
data₁ to the imaging apparatus in a removable condition;

reading, from a retrieve condition storage component of the imaging
apparatus, retrieve condition data₁ such as a key image or a keyword₁ for use as a retrieve
condition when performing image retrieval ~~for the image data stored on the image storage~~
~~component connected to the imaging apparatus;~~

retrieving a retrieval result by searching for [[the]] image data that matches
or is similar to the retrieve condition data from among the plurality of image data stored in
the image storage component; and

storing ~~inside~~ the retrieval result in an internal storage component of the
imaging apparatus ~~in an accumulative manner the image data that was retrieved until there~~
~~is an explicit delete instruction,~~

wherein the step of retrieving retrieval result further comprises the step
of, even [[when]] in a case where the image storage component [[was]] is detached from
the imaging apparatus [[or was]] and is replaced with a different image storage component,
further retrieving a retrieval result from among a plurality of image data stored in the
different image storage component using the common retrieve condition data which has
been used with respect to the image storage component, and

wherein retrieved retrieval results are accumulatively stored in the internal
storage component until there is an explicit delete instruction.

23. (Currently Amended) A computer-readable storage medium storing a
computer-executable computer program that causes a computer equipped with an image
storage component that stores a plurality of image data and is connected to the computer in
a removable condition, a retrieve condition storage component that stores retrieve
condition data such as a key image or a keyword for use as a retrieve condition when
performing image retrieval ~~with respect to the image data stored on the image storage~~
~~component that is connected to the computer,~~ and an internal storage component that

accumulatively stores ~~[[the]] a retrieval result image data that was retrieved by the image retrieval, to implement the steps of~~ execute a method comprising the steps of:

reading, from the retrieve condition storage component, [[the]] retrieve condition data such as a key image or a keyword for use as a ~~from the retrieve condition storage component;~~

retrieving a retrieval result by searching for [[the]] image data that matches or is similar to the retrieve condition data from among the plurality of image data stored in the image storage component; and

storing inside the retrieval result in the internal storage component of the computer ~~in an accumulative manner the image data that was retrieved until there is an explicit delete instruction,~~

wherein the step of retrieving a retrieval result further comprising the step of, even [[when]] in a case where the image storage component [[was]] is detached from the imaging apparatus or was computer and is replaced with a different image storage component, further retrieving a retrieval result from among a plurality of image data stored in the different image storage component using the common retrieve condition data which has been used with respect to the image storage component, and

wherein retrieved retrieval results are accumulatively stored in the internal storage component until there is an explicit delete instruction.

24. to 30. (Cancelled)